GNOMO

GNOMO | Industrial Pendant Light

Gnomo Industrial Pendant Light

6,90 Kg



50K HOURS LED LIFETIME L90B10 | 100K HOURS LED LIFETIME L80B10 | CE | IP65 | IK07 | >80 CRI | RG 0

-20° +40° | IN | 850° | ON OFF | DALI | PUSH DIM | 230V | 50/60 HZ

On request: HACCP

GNOMO | Industrial Pendant Light

Light source	Watt LED*	Lumen LED	Lumen OUT**	Energy rating***	Emission	Power supply	K	Colour
LED	116W	20210	15903	C (A↑G)	DIFFUSING	ON OFF DALI PUSH-DIM	4000K	Inox
LED	170W	28312	21350	C (A↑G)				

Standby Power: 0 | Mains Standby Power: 0 | Power Int.: 230 Vac 50Hz
*LED Power **Total Luminaire Output Flux @Tamb 25° - 4000°K ***This product contains a light source with Energy Efficiency Class C. Consider an 8% reduction in output flux for 3000°K LED sources, and 10% for CRI>90 LED sources.

APPLICATIONS

- Interior lighting fixture for production areas, industrial, commercial, and exhibition spaces.
- Suitable for use in the food industry in the version with methacrylate diffuser (HACCP).
- Certified for use from -20° to +40°C.
- For specific applications, please contact our technical department.

MECHANICS

- Anodized aluminum power supply housing.
- Powder-coated for high resistance to atmospheric agents and UV rays.
- Polished aluminum reflector for high luminous efficiency and chemical resistance.
- LED module specially designed to ensure maximum performance and efficiency.
- 5mm thick tempered safety glass resistant to thermal shock and impact.
- All fastenings are made with 2.5-3% molybdenum-rich stainless steel screws.
- Annealed silicone gaskets.
- Complete with plastic cable gland and 0.5-1m long output cable.
- IK07 impact protection.
- Complete with waterproof connector for line connection.
- IP65 protection - dustproof and protected from water jets.
- Insulation class I.

ALIMENTATIONS

- Electronic power supply integrated into the fixture body.
- Available in standard (ON-OFF) and dimmable (DALI) and (PUSH-DIM) versions.
- Power supply: 220-240 VAC 50/60 Hz.
- 3/5-pin terminal block.



LED source replaceable only by a qualified technician.

Power supply replaceable only by a qualified technician.

GNOMO small E | Industrial Pendant Light

Gnomo Small-E Industrial Pendant Light

5,70 Kg



50K HOURS LED LIFETIME L90B10 | 100K HOURS LED LIFETIME L80B10 | CE | IP65 | IK07 | >80 CRI | RG 0

-20° +40° | IN | 850° | ON OFF | DALI | PUSH DIM | 230V | 50/60 HZ

On request: HACCP

GNOMO small E | Industrial Pendant Light

Light source	Watt LED*	Lumen LED	Lumen OUT**	Energy rating***	Emission	Power supply	K	Colour
LED	138W	20230	15740	D (A↑G)	DIFFUSING	ON OFF DALI PUSH-DIM	4000K	Inox
LED	162W	24750	17183	D (A↑G)				
LED	168W	28215	21378	C (A↑G)				

Standby Power: 0 | Mains Standby Power: 0 | Power Supply: 230 Vac 50Hz
*LED Power **Total Luminaire Output Flux @Tamb 25° - 4000°K ***This product contains a light source with Energy Efficiency Class D, C
Consider an 8% reduction in output flux for 3000°K LED sources, and 10% for CRI>90 LED sources

APPLICATIONS

- Indoor and outdoor lighting fixture for production areas, industrial, commercial, and exhibition spaces.
- Suitable for use in the food industry in the version with methacrylate diffuser (HACCP).
- Certified for use from -20° to +40°C.
- For specific applications, please contact our technical department.

MECHANICS

- Anodized aluminum power supply housing.
- Powder-coated for high resistance to atmospheric agents and UV rays.
- Polished aluminum reflector for high luminous efficiency and chemical resistance.
- LED module specially designed to ensure maximum performance and efficiency.
- 5mm thick tempered safety glass resistant to thermal shock and impact.
- All fastenings are made with 2.5-3% molybdenum-rich stainless steel screws.
- Annealed silicone gaskets.
- Complete with plastic cable gland and 0.5-1m long output cable.
- IK07 impact protection.
- Complete with waterproof connector for line connection.
- IP65 protection - dustproof and protected from water jets.
- Insulation class I.

ALIMENTATIONS

- Electronic power supply integrated into the fixture body.
- Available in standard (ON-OFF) and dimmable (DALI) and (PUSH-DIM) versions.
- Power supply: 220-240 VAC 50/60 Hz.
- 3/5-pole terminal block.