



SATURNO

SATURNO | sospensione



LED lighting body for suspension installation with a circular shape of diam. 600mm, 900mm and 1200mm, made of extruded rolled aluminum profile and without welding points, powder coated and supplied with suspension kit complete with cables L.1500mm. Suitable for lighting halls, conference rooms, multifunctional environments or prestigious private residences. The extremely reduced profile makes the device light and extremely versatile for various uses. Thanks to the special one-piece anti-glare diffuser in opal methacrylate, the fixture is suitable for installation in workplaces with the presence of operators for long periods.

Source
LED module specially designed to ensure maximum uniformity and the total absence of point light.

Optics
Roto-symmetrical (see table opposite) protected by an opal methacrylate screen designed to reduce glare.

Power supply
Electronic power supply integrated in the body of the fixture, available in standard (on-off) and dimmable (DALI) versions. Power supply 220-240Vac 50 / 60Hz.

Saturno mini sospensione 600mm Saturno medium sospensione 900mm Saturno maxi sospensione 1200mm

8,50 Kg
Spessore 130mm

110 |

diam. est. Ø600
diam. int. Ø310
Cavo max 1500mm

11,00 Kg
Spessore 130mm

110 |


diam. est. Ø900
diam. int. Ø610
Cavo max 1500mm

14,00 Kg
Spessore 130mm

110 |


diam. est. Ø1200
diam. int. Ø910
Cavo max 1500mm

SATURNO sospensione								
Sorgente Light source	Watt LED*	Lumen OUT**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED SMD	20W	1960	600		3.000° K 4.000° K	ON-OFF On demand DALI	Wide flood (115°)	white
LED SMD	32W	2940	900					grey
LED SMD	49W	4460	1200					black corten
P. Stand-by: 0 P. Stand-by in rete: 0 Int. Elettrica: 230 Vac 50Hz *LED power **Total flow exiting the appliance @Tamb 25° - 4000°K ***This product contains an Energy Efficiency Class light source F, G Consider a reduction in output flow dell'8% by source LED 3000°K								



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
Power supply replaceable only by a qualified technician



On demand:

