

A modern office interior featuring a curved grey sofa, two large circular pendant lights, and a glass-walled meeting room. The space is bright with large windows overlooking a city. The floor is covered in a dark grey carpet with a subtle geometric pattern. A wooden slatted partition is visible behind the sofa.

URANO

URANO | sospensione



LED lighting body for suspension installation with a circular shape of diam. 600mm, 900mm and 1200mm, made of extruded rolled aluminum profile and without welding points, powder coated and supplied with suspension kit complete with cables L.1500mm. Suitable for lighting halls, conference rooms, multifunctional environments or prestigious private residences. The extremely reduced profile makes the device light and extremely versatile for various uses. Thanks to the special one-piece anti-glare diffuser in opal methacrylate, the fixture is suitable for installation in workplaces with the presence of operators for long periods.

Source
LED module specially designed to ensure maximum uniformity and the total absence of point light.

Optics
Roto-symmetrical (see table opposite) protected by an opal methacrylate screen designed to reduce glare.

Power supply
Electronic power supply integrated in the body of the fixture, available in standard (on-off) and dimmable (DALI) versions. Power supply 220-240Vac 50 / 60Hz.


Urano mini sospensione 600mm

7,30 Kg
Spessore 80mm

110 | 
diam. est. Ø600
diam. int. Ø450
Cavo max 1500mm


Urano medium sospensione 900mm

9,70 Kg
Spessore 80mm

110 | 
diam. est. Ø900
diam. int. Ø750
Cavo max 1500mm


Urano maxi sospensione 1200mm

11,80 Kg
Spessore 80mm

110 | 
diam. est. Ø1200
diam. int. Ø1050
Cavo max 1500mm


URANO sospensione									
Sorgente Light source	Watt LED*	Lumen OUT**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour	
LED SMD	40W	2800	600		3.000° K 4.000° K	ON-OFF On demand DALI	Wide flood (115°)		white
LED SMD	56W	4000	900						grey
LED SMD	72W	5200	1200						black
									corten

P. Stand-by: 0 | P. Stand-by in rete: 0 | Int. Elettrica: 230 Vac 50Hz
*LED power **Total flow exiting the appliance @Tamb 25° - 4000°K ***This product contains an Energy Efficiency Class light source G
Consider a reduction in output flow dell'8% by source LED 3000°K



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
Power supply replaceable only by a qualified technician



On demand:

DALI



