




FLO




FLO | Recessed






Flo recessed flush-fitting
0,45 Kg



Flo Recessed Backlogged
0,45 Kg



Formwork for the installation of the
flush-mounted version



FLO Recessed				
Watt*	Lumen**	øDiameter mm	K	Emission
9W	1000	83,5	3000 K 4000 K	Medium (31°) Flood (51°)
	1000	100		

Standby Power: 0 | Main Standby Power: 0 | Current: 350mA
*LED Power **Total Luminaire Output @ Tamb 25° ~ 4000°K
Consider an 8% reduction in output flux for 3000°K LED sources

Colours



Charateristics



On request:








FLO MAXI | Recessed



Flo recessed flush-fitting Maxi




0,55 Kg






Flo Recessed Backlogged Maxi



0,55 Kg



Formwork for the installation of the flush-mounted version



FLO MAXI | Recessed

Watt*	Lumen**	øDiameter mm	K	Emission
23W	2300	114	3000 K 4000 K	Medium (31°) Flood (51°)
	2300	130		

Standby Power: 0 | Mains Standby Power: 0 | Current: 700mA
 *LED Power **Total Luminaire Output @Tamb 25° - 4000°K
 Consider an 8% reduction in output flux for 3000°K LED sources

Colours



Characteristics



On request:






FLO WALL WASHER | Recessed flush-fitting



Flo Wall Washer recessed flush-fitting



FLO WALL WASHER recessed flush-fitting			
Watt*	Lumen**	K	Emission
4W	352	3000 K 4000 K	Spot (20°) Medium (40°) Flood (60°)
7W	616		
10W	880		
15W	1309		

Standby Power: 0 | Mains Standby Power: 0 | Power Int.: 100mA, 180mA, 250mA, 350mA
*LED Power **Total Luminaire Output @ Tamb 25° - 4000°K
Consider an 8% reduction in output flux for 3000°K LED sources

Colour



Charateristics



On request:

