
TEX BRIVIDO | Industrial projector




Tex 2 brivido

5,90 Kg




Drilling measurements
support bracket



TEX BRIVIDO | Industrial projector for temperatures from -40°C to +25°C

Light source	Relamping	Lumen LED	Watt LED*	Lumen OUT**	*Energy rating****	*Emission*	*Power supply*	K	*Colour*
COB LED	400W	165W	26235	22300	D (A↑G)	CONCENTRATING DIFFUSING ASYMMETRIC 1 ASYMMETRIC 2	ON-OFF	3000K 4000K	Inox Black

Standby Power: 0 | Mains Standby Power: 0 | Power Int.: 230 Vac 50Hz
*LED Power **Total Luminaire Output @Tamb 25° - 4000°K ***This product contains a light source with Energy Efficiency Class D. Consider an 8% reduction in output flux for 3000° LED sourceK





APPLICATIONS

- Lighting fixture designed for use in cold rooms, refrigerated warehouses, blast chillers, and outdoor environments
- with negative temperatures.
- Fixtures suitable for use in the food industry (HACCP).
- Certified for use from -40°C to +25°C.
- For specific applications, please contact our technical department.


MECHANICS

- Anodized aluminum body with heatsink function.
- Painted, press-bent aluminum frame.
- Adjustable, press-bent steel bracket.
- Powder-coated bracket provides high resistance to atmospheric agents and UV rays.
- COB LED specially designed to ensure maximum performance and efficiency.
- Removable, molded silicone optical unit (IP65 rated).
- Narrow, Wide, Asymmetric 1, and Asymmetric 2 emission options.
- All fastenings are made with 2.5-3% molybdenum-rich stainless steel screws.
- Annealed silicone gaskets.
- Complete with plastic cable gland and 0.5-1m long output cable.
- IK09 impact protection.
- Complete with waterproof connector for line connection.
- IP65 protection - dustproof and protected from water jets.
- Insulation class I.


ALIMENTATIONS

- Electronic power supply integrated into the body of the fixture.
- Available in the Standard (ON-OFF) version.
- Power supply: 220-240 VAC 50/60 Hz.
- 3-pole terminal block.





LED source replaceable only by a qualified technician.



Power supply replaceable only by a qualified technician.