



NAIROBI

NAIROBI | apparecchio da terra

Lighting fixture for pedestrian and vehicular paths with direct emission, the minimal design and the lightness of the lamp body make it suitable for outdoor installations without being bulky. Lamp composed of a stem in extruded aluminum profile and subsequently powder-coated to provide high resistance to atmospheric agents and UV rays, luminescent head made of anti-UV satin polycarbonate, which acts as a protection for the LED module, fixed by resin flush with the body of the appliance to allow water and dirt to flow out. IP67 protection both on the product and on the cable using IP67 connectors.

Source
LED module specially designed to ensure maximum uniformity.

Optics
Roto-symmetrical optic (see table on the side) protected by a UV-resistant opal polycarbonate screen.

Power supply
Electronic power supply integrated into the body of the fixture, available in standard versions (on-off). Power supply 220-240Vac 50 / 60Hz.

Note
We recommend the use of the SPD protection device, supplied by us upon request.



Nairobi

1,70 Kg

Ø100

80

420

NAIROBI apparecchio da terra							
Sorgente Light source	Watt LED*	Lumen OUT**	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED	7W	440	G A G	3.000° K	ON-OFF	Flood (48°)	anthracite

P. Stand-by: 0 | P. Stand-by in rete: 0 | Int. Elettrica: 230 Vac 50Hz
*LED power **Total flow exiting the appliance @ Tamb 25° - 3000°K ***This product contains an Energy Efficiency Class light source G

Connectors



Socket-plug




3-way "T" type




On demand:

SPD



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician



Alimentatore non sostituibile
Non-replaceable power supply

Request the replacement manual from our technical offices



