

ORFEO

ORFEO | sospensione





Circular LED luminaire for suspended installation with diameters of 600mm, 900mm and 1200mm, made of rolled extruded aluminum profile with no welding points, powder coated and supplied with suspension kit complete with cables L.2000mm. Suitable for lighting halls, conference rooms, multi-purpose environments or prestigious private residences. The extremely reduced profile makes the fixture light and extremely versatile for various uses. Thanks to the special one-piece anti-glare opal methacrylate diffuser, the luminaire is suitable for installation in workplaces with the presence of operators for long periods. Characterized by an internal emission.


Source
LED module specially designed to ensure maximum uniformity and the total absence of point light.

Optics
Rotosymmetrical (see table alongside) protected by an opal methacrylate screen designed to reduce glare.

Power supply
Electronic ballast integrated in the body of the fixture, available in the standard versions (on-off). Power supply 220-240Vac 50/60Hz.


Orfeo mini sospensione 600mm	Orfeo medium sospensione 900mm	Orfeo maxi sospensione 1200mm
 3,30 Kg Spessore 30mm	 4,70 Kg Spessore 30mm	 5,80 Kg Spessore 30mm
20 	20 	20 
diam. est. Ø600 diam. int. Ø540 Cavo max 1500mm	diam. est. Ø900 diam. int. Ø840 Cavo max 1500mm	diam. est. Ø1200 diam. int. Ø1140 Cavo max 1500mm

ORFEO sospensione								
Sorgente Light source	Watt LED*	Lumen OUT**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED SMD	30W	1800	600		3.000° K	ON-OFF	Medium (30°)	 white
LED SMD	45W	2500	900					 black
LED SMD	60W	3500	1200					 gold
								 silver
P. Stand-by: 0 P. Stand-by in rete: 0 Int. Elettrica: 230 Vac 50Hz *LED power **Total flow exiting the appliance @Tamb 25° - 3000°K ***This product contains an Energy Efficiency Class light source G Consider a reduction in output flow dell'8% by source LED 3000°K								



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
Power supply replaceable only by a qualified technician



