



TETRIX

TETRIX | sospensione




LED lighting body for suspended installation, the square model has dimensions 820x820mmm, the rectangular version has dimensions 820x420 while the L version has a more particular design (dimensions see drawings alongside), made of extruded and squared aluminum profile without welding points, powder coated and supplied with suspension kit complete with cables L.1500mm. Suitable for lighting halls, conference rooms, multifunctional environments or prestigious private residences. The extremely small profile makes the device light and extremely versatile for various uses. Thanks to the special one-piece anti-glare diffuser in opal methacrylate, the luminaire is suitable for installation in workplaces with the presence of operators for long periods.

Source
LED module specially designed to guarantee maximum uniformity and the total absence of point light.


Optics
Rotosymmetric (see table alongside) protected by an opal methacrylate screen designed to reduce glare.

Power supply
Electronic driver integrated into the body of the luminaire, available in standard (on-off) and dimmable (DALI) versions. Power supply 220-240Vac 50/60Hz.


Tetrix rectangle sospensione




Tetrix L sospensione



Tetrix square sospensione




TETRIX sospensione								
Sorgente <i>Light source</i>	Watt LED*	Lumen OUT**	Lunghezza mm <i>Length mm</i>	Classe Energetica <i>Energy rating***</i>	K	Alimentazione <i>Power supply</i>	Emissione <i>Emission</i>	Colore <i>Colour</i>
LED SMD	50W	7800	820X420		3.000° K 4.000° K	ON-OFF On demand DALI	Wide flood (115°)	white grey black corten
LED SMD	75W	11800	820x820x420					
LED SMD	100W	15900	820x820					
P. Stand-by: 0 P. Stand-by in rete: 0 Int. Elettrica: 230 Vac 50Hz *LED power **Total flow exiting the appliance @Tamb 25° - 4000°K ***This product contains an Energy Efficiency Class light source E Consider a reduction in output flow dell'8% by source LED 3000°K								



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
Power supply replaceable only by a qualified technician



On demand:



