

NETTUNO | sospensione



Circular LED luminaire for suspended installation with diameters of 600mm, 900mm and 1200mm, made of rolled extruded aluminum profile with no welding points, powder coated and supplied with suspension kit complete with cables L.4000mm. Suitable for lighting halls, conference rooms, multi-purpose environments or prestigious private residences. The extremely reduced profile makes the fixture light and extremely versatile for various uses. Thanks to the special one-piece anti-glare opal methacrylate diffuser, the luminaire is suitable for installation in workplaces with the presence of operators for long periods.


Source
 LED module specially designed to ensure maximum uniformity and the total absence of point light.

Optics
 Rotosymmetrical (see table alongside) protected by an opal methacrylate screen designed to reduce glare.

Power supply
 Electronic ballast integrated in the body of the fixture, available in the standard versions (on-off). Power supply 220-240Vac 50/60Hz.

Nettuno mini sospensione 600mm

3,30 Kg
 Spessore 15mm



diam. est. Ø600
 diam. int. Ø570
 Cavo max 4000mm

Nettuno medium sospensione 900mm


4,70 Kg
 Spessore 15mm



diam. est. Ø900
 diam. int. Ø870
 Cavo max 4000mm


Nettuno maxi sospensione 1200mm

5,80 Kg
 Spessore 15mm




diam. est. Ø1200
 diam. int. Ø1170
 Cavo max 4000mm

NETTUNO sospensione								
Sorgente Light source	Watt LED*	Lumen OUT**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED SMD	33W	2000	600		3.000° K	ON-OFF	Wide Flood (120°)	white black
LED SMD	48W	3000	900					
LED SMD	66W	4000	1200					
P. Stand-by: 0 P. Stand-by in rete: 0 Int. Elettrica: 230 Vac 50Hz *LED power **Total flow exiting the appliance @Tamb 25° - 3000°K ***This product contains an Energy Efficiency Class light source G Consider a reduction in output flow dell'8% by source LED 3000°K								



Sorgente LED sostituibile solo da tecnico abilitato
 LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
 Power supply replaceable only by a qualified technician

