

BOGOTA' | plafone



LED luminaire for ceiling installation, suitable for lighting residential and commercial outdoor environments. Thanks to the special anti-glare diffuser in thermoformed methacrylate, it always guarantees perfect lighting while maintaining high visual comfort and the absence of punctiform lighting. Powder coated ABS body to provide high resistance to atmospheric agents and UV rays. Ceiling fixing system using a treated aluminum alloy plate. It can be installed on any flat surface using the brick plugs supplied.

Source
LED module specially designed to ensure maximum uniformity and the absence of punctiform light.


Optics
Rotosymmetric emission (see table alongside) protected by a thermoformed methacrylate screen designed to reduce glare.

Power supply
Electronic ballast integrated in the body of the fixture, available in the standard (on-off), dimmable (DALI) or with Emergency system version. Power supply 220-240Vac 50/60Hz.

Note
We recommend the use of the SPD protection device, supplied by us upon request.

Bogotá plafone

1,80 Kg




BOGOTA' plafone								
Sorgente Light source	Watt*	Lumen**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED	12W	1500	270		3.000° K 4.000° K	ON-OFF	Wide flood (116°)	white
LED	22W	2500	377			On demand DALI		

P. Stand-by: 0 | P. Stand-by in rete: 0 | Int. Elettrica: 230 Vac 50Hz
*LED power **Total flow exiting the appliance @Tamb 25° - 3000°K ***This product contains an Energy Efficiency Class light source E

Connectors




Connectors IP



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician

Request the replacement manual from our technical offices



Alimentatore sostituibile solo da tecnico abilitato
Power supply replaceable only by a qualified technician

100K
HOURS
LED LIFETIME
L70B50

60K
HOURS
LED LIFETIME
L90B10

RG 0

850°

IK09

IN

>90
CRI

IP65

ON
OFF

On demand:

EM
EN 60598-2-22

DALI

SPD

