



POLIFEMO



POLIFEMO | plafone



LED luminaire for ceiling installation. Suitable for enhancing elevations and covering materials, the reduced design makes the luminaire perfectly integrated with any type of architecture. Body and passive dissipation system made of anodized aluminum alloy and subsequently powder painted to provide high resistance to atmospheric agents and UV rays. Can be installed on any flat surface by tessellation. Tempered glass diffuser with satin “frost” effect designed to reduce glare, held in position by resin.

Source
LED module specially designed to ensure maximum uniformity.

Optics
Rotosymmetric emission (see table alongside) protected by a glass screen with a satin “frost” effect designed to reduce glare.

Power supply
Electronic ballast integrated in the body of the fixture, available in the standard version (on-off). Power supply 220-240Vac 50/60Hz.

Note
We recommend the use of the SPD protection device, supplied by us upon request.

Polifemo maxi plafone	Polifemo medium plafone	Polifemo mini plafone	Polifemo micro plafone
0,90 Kg	0,70 Kg	0,60 Kg	0,50 Kg

POLIFEMO plafone								
Sorgente Light source	Watt LED*	Lumen OUT**	ØDiametro mm ØDiameter mm	Classe Energetica Energy rating***	K	Alimentazione Power supply	Emissione Emission	Colore Colour
LED	7W	600	65		3000 K	ON-OFF	Wide flood (119°)	bianco nero
LED	17W	1350	80					
LED	21W	1830	95					
LED	30W	2710	120					

P. Stand-by: 0 | P. Stand-by in rete: 0 | Int. Elettrica: 230 Vac 50Hz
*Potenza dei LED **Flusso totale in uscita dall'apparecchio @Tamb 25° - 3000°K ***Questo prodotto contiene una sorgente luminosa di Classe di efficienza Energetica G

Connectors




Connectors IP




On demand:

SPD



Sorgente LED sostituibile solo da tecnico abilitato
LED source replaceable only by a qualified technician



Alimentatore non sostituibile
Non-replaceable power supply

Request the replacement manual from our technical offices

