



WILLER

WILLER | Waterproof Ceiling Light

Willer

2,50 Kg

3,40 Kg

1200

1500

95

118

50K HOURS LED LIFETIME L90B10

100K HOURS LED LIFETIME L80B10

CE

IP66

IK10

>80 CRI

HACCP

-15°

+45°

IN

850°

ON OFF

DALI

230V

50/60 HZ

On request:

>90 CRI

APPLICATIONS

- Interior lighting fixture for production areas, industrial, commercial, and exhibition spaces.
- Fixtures suitable for use in the food industry (HACCP).
- Certified for use from -15°C to +45°C.
- For specific applications, please contact our technical department.

MECHANICS

- Polycarbonate body for high impact and temperature resistance.
- LED module specially designed to ensure maximum performance and efficiency.
- Electronics specifically developed for use in both cold and hot environments.
- Transparent polycarbonate screen.
- Narrow, medium, and wide beam options.
- Molded polycarbonate end caps with a waterproof gasket and quick-connect connector.
- Complete with plastic cable gland (M20-M25) and 0.5-1m output cable.
- IK10 impact protection.
- Complete with waterproof connector for line connection.
- IP66 protection - dustproof and protected from water jets.
- Insulation class I.

ALIMENTATIONS

- Electronic power supply integrated into the fixture body.
- Available in standard (ON-OFF) and dimmable (DALI) versions.
- Power supply: 220-240 VAC 50/60 Hz.
- 3/5-pole terminal block.

LED source replaceable only by a qualified technician.

Power supply replaceable only by a qualified technician.

WILLER | Waterproof Ceiling Light

Light source	Watt LED*	Lumen LED	Lumen OUT**	Energy rating***	Emission	Power supply	K	Colour
LED	27W	3780	3213	D A G	CONCENTRATING MEDIUM DIFFUSING	ON OFF DALI	3000K 4000K	Grey
LED	40W	6480	5502	D A G				
LED HO	63W	8640	7344	C A G				

Standby Power: 0 | Mains Standby Power: 0 | Power Supply: 230 Vac 50Hz
*LED Power **Total Luminaire Output @Tamb 25° - 4000°K ***This product contains a light source with Energy Efficiency Class D, C
Consider an 8% reduction in output flux for 3000°K LED sources

Tipologia Accessori	Descrizione
	Wall mounting kit for product rotation
	Fixing clips in stainless steel 316L, 2 units
	Pendant kit



**WILLER
SYSTEM**

WILLER SYSTEM | Waterproof Ceiling Light

